

Package: diffr (via r-universe)

August 26, 2024

Title Display Differences Between Two Files using Codediff Library

Version 0.2

Description An R interface to the 'codediff' JavaScript library (a copy of which is included in the package, see <https://github.com/danvk/codediff.js> for information). Allows for visualization of the difference between 2 files, usually text files or R scripts, in a browser.

Depends R (>= 3.0)

Imports htmlwidgets

License GPL-2

LazyData true

RoxygenNote 7.3.1

Suggests shiny

BugReports <https://github.com/muschellij2/diffr/issues>

Repository <https://muschellij2.r-universe.dev>

RemoteUrl <https://github.com/muschellij2/diffr>

RemoteRef HEAD

RemoteSha 0208b621b0398b7c4c2db67291aa106c54fd32ee

Contents

diffr	2
diffrOutput	3

Index	5
--------------	----------

 diff

Diff 2 files side by side

Description

Takes the diff of 2 files and shows comparisons

Usage

```
diffr(
  file1,
  file2,
  contextSize = 3,
  minJumpSize = 10,
  wordWrap = TRUE,
  before = file1,
  after = file2,
  width = NULL,
  height = NULL
)
```

Arguments

file1	First file to take diff (usually original file)
file2	First file to take diff (usually updated file)
contextSize	Minimum number of lines of context to show around each diff hunk. (default: 3).
minJumpSize	Minimum number of equal lines to collapse into a “Show N more lines” link. (default: 10)
wordWrap	By default, code will go all the way to the right margin of the diff. If there are 60 characters of space, character 61 will wrap to the next line, even mid-word. To wrap at word boundaries instead, set this option.
before	Text to display on file1
after	Text to display on file2
width	passed to <code>createWidget</code>
height	passed to <code>createWidget</code>

Examples

```
library(diffr)
file1 = tempfile()
writeLines("hello, world!\n", con = file1)
file2 = tempfile()
writeLines(paste0(
  "hello world?\nI don't get it\n",
  paste0(sample(letters, 65, replace = TRUE), collapse = "")), con = file2)
diffr(file1, file2, before = "f1", after = "f2")
```

diffROutput *Wrapper functions for using diffR in shiny*

Description

Use `diffROutput` to create a UI element, and `renderDiffR` to render the diff.

Usage

```
diffROutput(outputId, width = "100%", height = "400px")

renderDiffR(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

<code>outputId</code>	Output variable to read from
<code>width, height</code>	The width and height of the diff (see shinyWidgetOutput)
<code>expr</code>	An expression that generates a <code>diffR</code> object
<code>env</code>	The environment in which to evaluate <code>expr</code>
<code>quoted</code>	Is <code>expr</code> a quoted expression (with <code>quote()</code>)? This is useful if you want to save an expression in a variable.

Widget output function for use in Shiny

Examples

```
library(diffR)
library(shiny)
file1 = tempfile()
writeLines("hello, world!\n", con = file1)
file2 = tempfile()
writeLines(paste0(
  "hello world?\nI don't get it\n",
  paste0(sample(letters, 65, replace = TRUE), collapse = "")), con = file2)

ui <- fluidPage(
  h1("A diffR demo"),
  checkboxInput("wordWrap", "Word Wrap",
    value = TRUE),
  diffROutput("exdiff")
)

server <- function(input, output, session) {
  output$exdiff <- renderDiffR({
    diffR(file1, file2, wordWrap = input$wordWrap,
      before = "f1", after = "f2")
  })
}
```

```
shinyApp(ui, server)
```

Index

`createWidget`, [2](#)

`diffr`, [2](#), [3](#)

`diffrOutput`, [3](#)

`renderDiffr (diffrOutput)`, [3](#)

`shinyWidgetOutput`, [3](#)